

Lightweight Anti-Static Polyurethane Vacuum Hose



- Applications** Suction and discharge of abrasive powders, fumes, shavings and vapours. Ideal as an alternative to PVC ducting when a higher working temperature is required.
- Tube** Polyurethane
- Reinforcement** Rigid PVC Spiral and Copper Wire
- Cover** Polyurethane
- Temperature** -20^oc to +80^oc
- Coil Size** 30mtrs (cut lengths: multiples of 5mtrs)
- Colour** Clear with Ivory Spiral

ID	Vacuum H2O	Bend Radius	Weight	Part No.
mm	Mtr	mm	Kg's/mtr	
32	2.5	35	0.155	0338198
38	2	50	0.195	0338200
40	2	60	0.2	0338202
45	2	65	0.245	0338204
52	2	70	0.29	0338206
60	1.6	80	0.425	0338208
63	1.6	80	0.46	0338210
70	1.6	95	0.5	0338212
76	1.6	100	0.55	0338214
80	1.6	110	0.59	0338216

ID	Vacuum H2O	Bend Radius	Weight	Part No.
mm	Mtr	mm	Kg's/mtr	
90	1.4	125	0.67	0338218
102	1.3	140	0.75	0338220
110	1.2	150	0.9	0338222
120	1	160	1	0338224
127	1	170	1.1	0338226
130	0.9	170	1.2	0338228
140	0.9	180	1.3	0338230
150	0.8	200	1.5	0338232
160	0.7	220	1.78	0338234



Telephone +44 (0)1384 480 197
 Facsimile +44 (0)1384 74840
 Email sales@cmflexibles.com
 Online www.cmflexibles.com