

Carbon Free Water Delivery



Applications	Used for cable covering/insulation and cooling hose on induction furnaces and general maintenance applications, manufactured from carbon free components.
Tube	Carbon Free Synthetic Rubber
Reinforcement	Synthetic Fabric Plies
Cover	Carbon Free Synthetic Rubber
Temperature	-35°C to +70°C
Coil Size	40mtr / 20mtr coils
Colour	Red

ID		OD		Working Pressure		Burst Pressure		Bend Radius	Weight	Part No.
mm	inch	mm	inch	psi	bar	psi	bar	mm	Kg's/mtr	
10	3/8	19	-	145	10	435	30	-	0.24	0919005
13	1/2	22	-	145	10	435	30	-	0.34	0919010
19	3/4	33	-	145	10	435	30	-	0.66	0919020
25	1	39	-	145	10	435	30	-	0.89	0919025
32	1 1/4	45	-	145	10	435	30	-	0.93	0919030
35	1 3/8	49	-	145	10	435	30	-	1.00	0919035
38	1 1/2	52	-	145	10	435	30	-	1.20	0919040
45	1 3/4	59	-	145	10	435	30	-	-	0919045
51	2	65	-	145	10	435	30	-	1.49	0919050
70	2 3/4	96	-	85	6	255	18	-	-	0919055
76	3	99	-	70	5	210	15	-	-	0919060



Telephone +44 (0)1384 480 197
 Facsimile +44 (0)1384 74840
 Email sales@cmflexibles.com
 Online www.cmtflexibles.com