

Smoothbore PTFE Lined Hose Assemblies



Description

PTFE lined Stainless Steel Overbraid Flexible Hose and Assemblies. Particularly suited to transfer of corrosive chemicals, food products, hydraulic oil and steam. Offers excellent flexibility and resistance to chemicals and solvents.

Construction

Internal - Smoothbore PTFE
External - 304 or 316 Braided Stainless Steel

Temperature

-60°C to +260°C

Assemblies

Made to order

Available in assembly form with a large range of terminations that include; Flanges (fixed and swivel), Fully-tapped Flanges, Cam and Groove, RJT, Din and traditional male and female threaded unions.

Contact our sales office with your assembly requirements for more info!

ID		Work Pressure	Burst Pressure	Bend Radius
mm	inch	bar	bar	mm
6.70	1/4	224	672	76
8.40	5/16	207	621	102
10.00	3/8	183	552	127
13.20	1/2	161	483	150
16.60	5/8	114	345	178
19.8	3/4	103	310	203



Telephone +44 (0)1384 480 197

Facsimile +44 (0)1384 74840

Email sales@cmtflexibles.com

Online www.cmtflexibles.com

22.1	7/8	92	276	229
26.10	1	80	241	305



Telephone +44 (0)1384 480 197
 Facsimile +44 (0)1384 74840
 Email sales@cmtflexibles.com
 Online www.cmtflexibles.com