

Whitewater



Applications	For use on either steam cleaner machines or combination steam cleaner/pressure washer machines.
Tube	Pryosyn Synthetic Rubber
Reinforcement	Braided Steel Wire
Cover	Hysunite Synthetic Rubber - RMA Class B (medium/high oil resistance)
Temperature	Handles steam at 163°C and 350 psi, handles hot water at 121°C and 3000 psi (2500 psi on ½")
Coil Size	152.4mtr coils
Colour	Black / Red

ID		OD		Working Pressure		Burst Pressure		Vacuum HG		Bend Radius	Weight	Part No.
mm	inch	mm	inch	psi	bar	psi	bar	mm	inch	mm	Kg's/mtr	
BLACK COVER												
9.53	3/8	17.53	0.69	350	24	1400	96	-	-	-	0.34	0749005
12.70	1/2	20.83	0.82	350	24	1400	96	-	-	-	0.48	0749010
RED COVER												
9.53	3/8	17.53	0.69	350	24	1400	96	-	-	-	0.34	0749105
12.70	1/2	20.83	0.82	350	24	1400	96	-	-	-	0.48	0749110



Telephone +44 (0)1384 480 197
 Facsimile +44 (0)1384 74840
 Email sales@cmtflexibles.com
 Online www.cmtflexibles.com