

Blue Flexwing



Applications	Handles the majority of today's industrial chemicals in pressure, gravity flow, or suction service.
Tube	Specular XLPE
Reinforcement	Spiral-plied synthetic fabric with double wire helix
Cover	EPDM - Versigard Synthetic Rubber (wrapped impression)
Temperature	-32°C to +66°C
Coil Size	30.5mtrs (6.1mtr cut lengths)
Colour	Blue

ID		OD		Working Pressure		Burst Pressure		Vacuum HG		Bend Radius	Weight	Part No.
mm	inch	mm	inch	psi	bar	psi	bar	mm	inch	mm	Kg's/mtr	
12.70	1/2	24.38	0.96	200	13.8	800	55	736.6	29	152	0.45	0737005
19.05	3/4	30.99	1.22	200	13.8	800	55	736.6	29	178	0.67	0737010
25.40	1	37.34	1.47	200	13.8	800	55	736.6	29	203	0.82	0737015
31.75	1 1/4	44.45	1.75	200	13.8	800	55	736.6	29	229	1.04	0737020
38.10	1 1/2	51.82	2.04	200	13.8	800	55	736.6	29	254	1.41	0737025
50.80	2	65.53	2.58	200	13.8	800	55	736.6	29	305	1.82	0737030
63.50	2 1/2	79.50	3.13	200	13.8	800	55	736.6	29	381	2.46	0737035
76.20	3	93.98	3.70	200	13.8	800	55	736.6	29	457	3.33	0737040
101.60	4	120.14	4.73	200	13.8	800	55	736.6	29	610	4.48	0737045
152.40	6	175.01	6.89	200	13.8	800	55	736.6	29	914	9.14	0737050



Telephone +44 (0)1384 480 197
 Facsimile +44 (0)1384 74840
 Email sales@cmtflexibles.com
 Online www.cmtflexibles.com