

Composite Hose

Product Datasheet



Technical Specification

1. Description

Danoil 7 Standard Duty a tough and high strength petroleum transfer hose. BS EN 13765: Type 3 BS5842: 1980.

2. Applications:

Rail car loading and unloading, road tanker bottom loading and lubricating oil transfer.

3. Inner Wire Helix

High tensile mild steel Galvanised

4. Outer Wire Helix

High tensile mild steel Galvanised

5. Tube

High tensile mild steel Galvanised

6. Sealing Film

Polypropylene

7. Cover

PVC Coated Polyester cloth

8. Temperature

-30°C to +100°C

9. Coil Size

In fitted assembly form to customer specification (Tested and Certificated)

10. Colour

Black

Inside Diameter		Outside Diameter		Working Pressure		Burst Pressure		Vacuum HG		Bend Radius	Weight	CMT Part Number
(mm)	(inch)	(mm)	(inch)	(psi)	(bar)	(psi)	(bar)	(mm)	(inch)	(mm)	(kg's/mtr)	
25	1	-	-	200	14	800	56	-	-	100	0.8	0803002
38	1 ½	-	-	200	14	800	56	-	-	140	1.2	0803004
50	2	-	-	200	14	800	56	-	-	180	1.9	0803006
65	2 ½	-	-	200	14	800	56	-	-	205	2.5	0803008
75	3	-	-	200	14	800	56	-	-	280	3.0	0803010
100	4	-	-	200	14	800	56	-	-	395	5.2	0803012

