

Fire Brigade Booster Black



- Applications** High pressure robust fire engine booster hose manufactured to the USA Forest Service Specification complying entirely with EN1947:2002-2-C-1
- Tube** Chemivic – Oil and abrasion resistant, safely handles temperatures up to 100°C.
- Reinforcement** Unique single ply polyester braid. This unique braid construction offers improved coupling retention under high and pulsating pressures over existing spiral polyester
- Cover** Chemivic– Oil, abrasion and excellent ozone resistant, smooth for ease of cleaning and reeling.
- Temperature** -18°C to +100°C
- Coil Size** 18.3, 54.9 and 91.5 mtrs (cut lengths available upon request)
- Colour** Black

ID		OD		Working Pressure		Burst Pressure		Bend Radius	Weight	Coil Length	Part No.
mm	inch	mm	inch	psi	bar	psi	bar	mm	Kg's/mtr	mtrs	
19.1	3/4	30.5	-	800	55	2400	165	-	0.55	18.3	0715005
19.1	3/4	30.5	-	800	55	2400	165	-	0.55	54.9	0715010
19.1	3/4	30.5	-	800	55	2400	165	-	0.55	91.5	0715015



Telephone +44 (0)1384 480 197
 Facsimile +44 (0)1384 74840
 Email sales@cmflexibles.com
 Online www.cmflexibles.com