

Product Datasheet



Technical Specification

1. Description

Fire Fighting Vehicle Reeling Hose to BSEN1947:2014.

2. Applications:

High pressure water reeling hose on fire fighting vehicles, with smooth, wear resistant and flame retardant cover.

3. Tube

Chemivac Oil and abrasion resistant, safely handles temperatures up to 100°C

4. Cover

Carbryn Oil resistant and flame retardant. Super abrasion resistance to withstand rough outdoor handling, smooth cover for ease of cleaning and reeling.

5. Reinforcement

Unique single ply polyester braid. This unique braid construction offers improved coupling retention under high and pulsating pressures over existing spiral polyester reinforced hose types.

6. Temperature

-18°C to +100°C

7. Coil Size

18.3, 54.9 and 91.5 mtrs (cut lengths available upon request)

8. Colour

Yellow (19mm available in Black)

Colour	Inside Diameter		Outside Diameter		Working Pressure		Burst Pressure		Length (m)	Weight (kg's/mtr)	CMT Part Number
	(mm)	(inch)	(mm)	(inch)	(psi)	(bar)	(psi)	(bar)			
Black	19.05	3/4	31.2	1.23	800	55	3200	220	18.3	0.70	0715005
Black	19.05	3/4	31.2	1.23	800	55	3200	220	54.9	0.70	0715010
Black	19.05	3/4	31.2	1.23	800	55	3200	220	91.5	0.70	0715015
Yellow	19.05	3/4	31.2	1.23	800	55	3200	220	18.3	0.70	0715016
Yellow	19.05	3/4	31.2	1.23	800	55	3200	220	54.9	0.70	0715018
Yellow	19.05	3/4	31.2	1.23	800	55	3200	220	91.5	0.70	0715019
Yellow	22.00	7/8	33.0	1.3	800	55	3200	220	18.3	0.80	0715004
Yellow	22.00	7/8	33.0	1.3	800	55	3200	220	36.6	0.80	0715002
Yellow	25.40	1	37.0	1.46	800	55	3200	220	20	0.95	0715031
Yellow	25.40	1	37.0	1.46	800	55	3200	220	40	0.95	0715032

