

Product Datasheet



Technical Specification

1. Description

High Pressure Spiral-Plied Wire Reinforced Steam Hose.

2. Applications:

250 PSI hose for steam service in refineries, chemical plants, ship-yards and industrial service. Recommended for cleaning, thawing and purging of pipe work. Extremely flexible for manual handling.

3. Tube

Versigard synthetic rubber

4. Cover

Versigard synthetic rubber, (wrapped impression)

5. Reinforcement

Spiral-plied steel wire

6. Temperature

-18°C to +208°C

7. Coil Size

30.5 mtrs and 91.5 mtrs (cut length: 15.24 mtrs or multiples of 15.24 mtrs)

8. Colour

Red (Yellow Spiral Stripe)

Inside Diameter (mm)	Inside Diameter (inch)	Outside Diameter (mm)	Outside Diameter (inch)	Working Pressure (psi)	Working Pressure (bar)	Burst Pressure (psi)	Burst Pressure (bar)	Vacuum HG (mm)	Vacuum HG (inch)	Bend Radius (mm)	Weight (kg's/mtr)	CMT Part Number
12.70	1/2	24.64	0.97	250	17	-	-	-	-	-	0.49	0780005
19.05	3/4	31.75	1.25	250	17	-	-	-	-	-	0.73	0780010
25.40	1	38.10	1.50	250	17	-	-	-	-	-	0.91	0780015
31.75	1 1/4	45.97	1.81	250	17	-	-	-	-	-	1.24	0780020
38.10	1 1/2	53.09	2.09	250	17	-	-	-	-	-	1.53	0780025
50.80	2	70.61	2.78	250	17	-	-	-	-	-	2.80	0780030



Telephone +44 (0)1384 480 197

Facsimile +44 (0)1384 74840

Email sales@cmtflexibles.com

Online www.cmtflexibles.com