

# Tan Flextra



|                      |                                                                                                                                                                                                             |
|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Applications</b>  | For tank truck and in-plant service. Used to convey non-oily abrasive materials such as sand, limestone, plastic pellets, and dry abrasive food products. Do not use where static electricity is a problem. |
| <b>Tube</b>          | Pureten Gum Rubber (FDA compliant)                                                                                                                                                                          |
| <b>Reinforcement</b> | Spiral-plied synthetic fabric with wire helix                                                                                                                                                               |
| <b>Cover</b>         | Plioflex Gum Rubber corrugated (wrapped impression)                                                                                                                                                         |
| <b>Temperature</b>   | -40 <sup>o</sup> c to +82 <sup>o</sup> c                                                                                                                                                                    |
| <b>Coil Size</b>     | 30.5mtr coils (cut lengths available on request)                                                                                                                                                            |
| <b>Colour</b>        | Tan                                                                                                                                                                                                         |

| ID    |      | OD     |      | Working Pressure |     | Burst Pressure |     | Vacuum HG |      | Bend Radius | Weight   | Part No. |
|-------|------|--------|------|------------------|-----|----------------|-----|-----------|------|-------------|----------|----------|
| mm    | inch | mm     | inch | psi              | bar | psi            | bar | mm        | inch | mm          | Kg's/mtr |          |
| 50.8  | 2    | 66.04  | 2.60 | 75               | 5   | 300            | 20  | 736.6     | 29   | 102         | 1.80     | 0766005  |
| 76.2  | 3    | 92.20  | 3.63 | 75               | 5   | 300            | 20  | 736.6     | 29   | 152         | 2.89     | 0766015  |
| 101.6 | 4    | 119.13 | 4.69 | 75               | 5   | 300            | 20  | 736.6     | 29   | 229         | 4.08     | 0766025  |
| 127.0 | 5    | 146.81 | 5.78 | 75               | 5   | 300            | 20  | 736.6     | 29   | 305         | 6.34     | 0766035  |



Telephone +44 (0)1384 480 197  
 Facsimile +44 (0)1384 74840  
 Email [sales@cmflexibles.com](mailto:sales@cmflexibles.com)  
 Online [www.cmflexibles.com](http://www.cmflexibles.com)