

Product Datasheet



Technical Specification

1. Description

Oil resistant Tube and Cover Multi-Purpose Hose, Electrically Conductive Through the Wall.

2. Applications:

Air, water, oil and dilute chemicals with the benefit of electrically conductive tube and cover where static is a consideration. It is also silicone free, suitable for paint spray environments. Ozone and UV resistant.

3. Tube

Nitrile Synthetic Rubber

4. Cover

Nitrile Synthetic Rubber - Ozone and UV Resistant

5. Reinforcement

Spiral Synthetic Yarn

6. Temperature

Petroleum Based Hydraulic Fluids -40°C to +150°C
Water and Air -25°C to + 85°C

7. Coil Size

25 mtr or 50 mtr coils

8. Colour

Black/Brown longitudinal stripes

Inside Diameter		Outside Diameter		Working Pressure		Burst Pressure		Vacuum HG		Bend Radius	Weight	CMT Part Number
(mm)	(inch)	(mm)	(inch)	(psi)	(bar)	(psi)	(bar)	(mm)	(inch)	(mm)	(kg's/mtr)	
6	1/4	13	1/2	290	20	870	60	-	-	25	0.16	0931002
8	5/16	15.6	5/8	290	20	870	60	-	-	35	0.21	0931004
10	3/8	17.6	11/16	290	20	870	60	-	-	40	0.25	0931006
13	1/2	21	13/16	290	20	870	60	-	-	55	0.32	0931008
16	5/8	25	1	290	20	870	60	-	-	65	0.43	0931010
19	3/4	29	1 1/8	290	20	870	60	-	-	85	0.55	0931012
25	1	36	1 7/16	290	20	870	60	-	-	115	0.76	0931014

